

QD086

Hand Formable

Features:

- * Hand formable
- * Quick and easy assembly

Applications:

- * Instrumentation
- * Laboratory test
- * Interconnection

Electrical


Frequency:	DC~40GHz
Cut-off Frequency:	61GHz
Impedance:	50Ω
Velocity of Propagation:	70%
Shielding Effectiveness:	100dB min.
Voltage Withstand:	1000V DC

Mechanical

Bend Radius (installation):	10mm
Bend Radius (repeated):	20mm
Weight:	20g/m

Environmental

Temperature:	-55~+150°C
--------------	------------

Construction


No.	Name	Size (mm)	Material
1	Inner Conductor	0.53	Silver-plated copper
2	Dielectric	1.65	PTFE
3	Inner Shield	2.17	Tin-plated copper braid

Attenuation & Power Handling

Frequency (GHz)	0.1	0.3	0.5	1	2	4	6	12	18	26.5	40
Attenuation*1 (dB/100m, typ.)	21.7	38.2	49.8	71.9	104.6	153.8	193.8	291.6	373.6	476.6	622.6
Average Power*2 (W)	237	135	103	72	49	33	27	18	14	11	8

[1] VSWR:1.0; Ambient: +25°C (77°F)

[2] VSWR:1.0; Ambient: +40°C (104°F); Sea level

Calculate Cable Attenuation: Attenuation (dB/100m) = $2.115000 * \sqrt{F} \text{ (MHz)} + 0.004990 * F \text{ (MHz)}$

Calculate Connector Attenuation: Attenuation (dB) = $0.03 * \sqrt{F} \text{ (GHz)}$

How To Order
QD086-X-Y-Z

X: Frequency in GHz

Y: Connector type

Z: Length in meters

Examples:

To order a QD086 cable assembly, DC-18GHz, SMA male to SMA female, 0.5 meter, specify QD086-18-SSF-0.5.

Connector naming rules:

2 - 2.4mm (40GHz, VSWR 1.8, typ.)

K - 2.92mm (40GHz, VSWR 1.8, typ.)

G - Mini-SMP (mateable with GPPO & SSMP, 40GHz, VSWR 1.8, typ.)

P - SMP (26.5GHz, VSWR 1.7, typ.)

A - SSMA (26.5GHz, VSWR 1.7, typ.)

S - SMA (26.5GHz, VSWR 1.7, typ. / 18GHz, VSWR 1.35 typ.)

N - N (18GHz, VSWR 1.35, typ.)

X - MMCX (6GHz, VSWR 1.3, typ.)

M - MCX (6GHz, VSWR 1.3, typ.)

B - BNC (4GHz, VSWR 1.4, typ.)

D - SMB (4GHz, VSWR 1.25, typ.)

Female Connector - Add 'F' after connector name

Right Angle - Add 'R' after connector name (VSWR increase 0.1)

Mating Connector

QCG-FB-086-1

SSMP female, Beryllium copper


QCG-FRB-086-2

SSMP female, Right angle, Beryllium copper


QCK-MG-086-3

2.92mm male, Stainless steel


QCK-FB-086-1

2.92mm female, Brass


QCK-FL2G-A220-1

2.92mm female, 2-hole flange mount, Stainless steel

QCK-FL4G-A220-1

2.92mm female, 4-hole flange mount, Stainless steel

QCP-FB-086-3

SMP female, Beryllium copper

QCP-FRB-086-1

SMP female right angle, Beryllium copper


QCP-FRB-086-2

SMP female right angle, Beryllium copper


QCA-MG-086-2

SSMA male, Stainless steel

QCA-FHB-086-1

SSMA female bulk head, Brass

QCS-FL2B-086-1

SMA female, 2-hole flange mount, Brass

QCS-FL4B-086-1

SMA female, 4-hole flange mount, Gold plated beryllium copper

QCS-FHB-086-2

SMA female bulk head, Gold plated brass


QCN-MB-086-1

N male, Nickel plated brass


QCN-FB-086-1

N female, Nickel plated brass


QCX-MB-086-1

MMCX male, Gold plated brass


QCX-MRB-086-1

MMCX male right angle, Gold plated brass


QCX-FB-086-1

MMCX female, Gold plated brass

QCM-MB-086-1

MCX male, Gold plated brass


QCM-MRB-086-2

MCX male right angle, Gold plated brass/beryllium copper


QCM-FB-086-1

MCX female, Gold plated brass

Semiflex RF Cables & Assemblies

QCS-MB-086-4

SMA male, Gold plated
brass

**QCS-MG-086-3**

SMA male, Stainless steel

**QCS-MRG-086-1**

SMA male right angle,
Stainless steel

**QCS-MRB-086-1**

SMA male right angle, Gold
plated brass

**QCS-FB-086-2**

SMA female, Gold plated
brass

**QCB-MB-086-1**

BNC male, Ternary alloy
plated brass

**QCD-MB-086-1**

SMB male, Gold plated
brass

QCD-MRB-086-1

SMB male right angle, Gold
plated brass

QCD-FB-086-1

SMB female, Gold plated
brass

QCD-FRB-086-1

SMB female right angle,
Gold plated brass