

## QPXO-110-5ET-165

### 110MHz, External Reference

Features:  
\* Low phase noise

Applications:  
\* Wireless  
\* Transceiver  
\* Laboratory Test

#### Electrical

Output Frequency (RF1/RF2):	110MHz
External Reference:	10MHz
Output Power:	5dBm min.
Spurious:	-70dBc max.
Harmonic:	-25dBc max.
Phase Noise:	-90dBc/Hz max.@10Hz
	-125dBc/Hz max.@100Hz
	-155dBc/Hz max.@1KHz
	-165dBc/Hz max.@10KHz
	-165dBc/Hz max.@100KHz
	-165dBc/Hz max.@1MHz
Voltage:	+12V DC
Current:	400mA max. (first)
	300mA max. (stable)
Impedance:	50Ω

#### Mechanical


Size*1:	51*60*20mm
	2.008*2.362*0.787in
RF Connectors:	SMA Female
Power Supply Connectors:	Feed Through/Terminal Post
Mounting:	4-M2.5 through-hole

[1] Exclude connectors.

#### Environmental

Operating Temperature:	-40~+75°C
Non-operating Temperature:	-55~+85°C

#### Outline Drawings



Unit: mm [in]  
Tolerance: ±0.2mm [±0.008in]

#### How To Order

### QPXO-110-5ET-165

Customization is available upon request.

Output Phase Noise

Measurement

DUT Info

Selected Trace  
 DUT Frequency 110.0000 MHz  
 DUT Power 7.8 dBm

Measurement Parameters

K (CH1/2) 0.282 / 0.286 V/rad  
 Tune Slope (CH1/2) 87 / 72 Hz/V  
 PLL BW 2.3 Hz  
 Correlations 10  
 Reference Internal References - Standard

