

QPAS-39000-48000-40-39S

39~48GHz, 40dB, 39dBm

Features:

- * Small Size
- * Low Power Consumption

Applications:

- * Wireless
- * Transmitter
- * Laboratory Test

Electrical

Frequency:	39~48GHz
Gain:	40dB typ.
Output Power (Psat):	39dBm typ.
Spurious:	-55dBc max.
Input VSWR:	2 typ.
Voltage:	+20V DC max.
Current:	10A max.
Impedance:	50Ω

Connector Wiring Definition

J30J-15ZKP			
Pin	Define	Function	Notes
1	TTL	RF Enable	RF on: 3.3V ~ 5 V
2	TTL-GND	Enabling	
3~7	+18V	VDC	
8~12	+18V-GND	GND	
13~15	NC	NC	

Mechanical

RF In Connectors:	2.4mm Female
RF Out Connectors:	BJ400
Power Supply Interface:	J30J-15ZKP

[1] Exclude connectors.

Environmental

Operating Temperature:	-40~+50°C
Non-operating Temperature:	-50~+60°C

Outline Drawings

To be done.

Unit: mm [in]
Tolerance: ±0.5mm [±0.02in]

How To Order

[QPAS-39000-48000-40-39S](#)

Customization is available upon request.