

# QPS2-300-18000-A

## SPDT, 0.3~18GHz, Absorptive

Features:  
 \* Low Insertion Loss  
 \* High Isolation

Applications:  
 \* Wireless  
 \* Transmitter  
 \* Laboratory Test  
 \* Radar

### Electrical

Frequency:	0.3~18GHz
Insertion Loss:	3.5dB max.
Isolation:	60dB min.
VSWR:	2 max.
Input Power:	20dBm max.
Voltage:	-5V, +5V DC
Current:	50mA max.
Control:	TTL High - 1 TTL Low/NC - 0

### Mechanical


Size <sup>*1</sup> :	25*17.5*10.2mm 0.984*0.689*0.402in
Switching Time:	35nS max.
RF Connectors:	SMA Female
Power Supply Connectors:	Feed Through/Terminal Post
Housing Material:	Aluminum, nickel plated
Mounting:	2-Φ2.7mm through-hole

[1] Exclude connectors.

### Environmental

Operating Temperature:	-45~+85°C
Non Operating Temperature:	-55~+125°C

### Outline Drawings



Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]

### Control True Table

C	Connection
0	J0 - j1 On
1	J0 - J2 On

### How To Order

**QPS2-300-18000-A**

Customization is available upon request.