

QWCK-650

WR-650, 1.13~1.73GHz


Features:
 * Broad Band
 * Low VSWR

Applications:
 * Calibration
 * Laboratory Test

Components

Part Number	Frequency (GHz)	VSWR (Max.)	Description	Material	Finish	Coating	Quantity (pcs)	Outline Drawings
QWCA-650-NF-R-2	1.13~1.73	1.2	Waveguide to coax adapter, WR-650 (BJ14) to N(f), right angle, FDP14	Aluminium	Conductive oxidation	Sea gray	2	Outline A
QWT650-25-A-2	1.13~1.73	1.04	Low power waveguide termination, WR-650 (BJ14), 25W, FDP14	Aluminium	Conductive oxidation	Sea gray	1	Outline B
QWS650-A-2	1.13~1.73	-	Waveguide short, WR-650 (BJ14), 12mm, FDP14	Aluminium	-	-	1	Outline D
QWSS650-69.86-A-2	1.13~1.73	-	1/4λ Waveguide straight section, WR-650 (BJ14), 69.86mm, FDP14	Aluminium	-	-	1	Outline C
Storage Box			Aluminum Alloy				1	-
Screw							1 set	-

Outline Drawings



Unit: mm [in] Tolerance: ±0.5mm [±0.02in]

Environmental

Operating Temperature: -40~+85°C

Non-operating Temperature: -50~+80°C

How To Order**QWCK-650** All the 5 components in one box.