

QPDO-E-10-39.4

External Reference, 10MHz, 39.4GHz

Features:

- * High Frequency Stability
- * Ultra Low Phase Noise

Applications:

- * Wireless
- * Transceiver
- * Laboratory Test
- * Radar

Electrical

Output Frequency:	39.4GHz
Output Power:	10dBm min.
Reference Input Power:	0~+5dBm
Output Spurious:	-68dBc max. @±(10MHz to 2GHz)
Output Harmonics:	-20dBc max. @9.85GHz, 19.7GHz, 29.55GHz
External Reference:	10MHz (-120dBc/Hz max. @10Hz -140dBc/Hz max. @100Hz -155dBc/Hz max. @1KHz -165dBc/Hz max. @10KHz -165dBc/Hz max. @100KHz)
Output Phase Noise:	-65dBc/Hz max. @100Hz -95dBc/Hz max. @1KHz -98dBc/Hz max. @10KHz -98dBc/Hz max. @100KHz -110dBc/Hz max. @1MHz
Voltage:	+12±0.5V
Current:	800mA max. (first) 600mA max. (stable)
Lock Indicator (LI):	TTL logic High: locked Low: unlocked


Environmental

Operating Temperature:	-55~+75°C
Non-operating Temperature:	-55~+85°C

Mechanical

Size*1:	57.2*57.2*33.8mm 2.252*2.252*1.331in
RF In Connectors:	SMA Female
RF Out Connectors:	2.92mm Female
Power Supply Interface:	Feed Through/Terminal Post
Mounting:	3-Φ3.2mm through-hole

[1] Exclude connectors.

Outline Drawings


Unit: mm [in]
Tolerance: ±0.2mm [±0.008in]

How To Order

QPDO-E-10-39.4

Customization is available upon request.